



# THERMOSHIELD

## Technical Bulletin- Interior

### Product Description

Interior is an internal coating ready to use. It is based on the thermal ceramic coating technology.

### Ingredients

polyacrylate- dispersion, titanium dioxide, kaolin, calcium carbonate, silicates, water, propylene glycol, cellulose, preservatives

### Product Group/ GIS-Code

Micro silicates, BSW10

### Area of application

Interior is a resistant preventive coating suitable for almost all internal surfaces. The special composition of ThermoShield Interior, provides a wide range of energetic application areas for thermal shielding both in summer and in winter.

### Product Properties

Variable diffusion, high resistance to aggressive environmental influences such as smog and ozone, low-emissions, free of solvents, high UV- and weather resistant, reflective, very high color resistance, thermally comforting, on the sorption- / diffusible subsoil dampening. [Material](#)

#### data

- sd-values according to DIN 52615
- dry area: sd = 1,7
- wet area: sd = 0,02
- density 1,12 kg/dm<sup>3</sup> according to ISO 2811-1
- fire behavior: B-s1, d0
- chemical resistance: available on request
- gloss: 0,4 according to DIN ISO 2813
- wet abrasion resistance: class 3 according to DIN-EN 13300
- contrast relation- covering power: class 2 according to DIN-EN 13300

### VOC ordinance (EG)

Limit value of 01.01.2010 for water based (Wb) coating material (Prod.-Cat. a) for interior painting on walls and ceilings (matt) = 30 g/l.

This product contains < 3 g/l VOC.

### Application information / Surface

Interior can be applied to all sound, clean, dry, rust-free and grease-free surfaces such as old and new plasters and intact previously painted surfaces. A pre-primed surface is recommended to guarantee energetic features.

### Surface preparation

#### Synthetics:

Analyze ability of adhesion

#### Metals:

Depending on metal and strain, prime with ThermoShield RustPrimer or ThermoShieldZinkPrimer

#### Non-workable previous coating:

Depending on coating, remove by washing, acid cleaning

#### Adhesion-interfering surfaces:

Wash, buck, grind

#### Absorbent substrates:

Primer with ThermoShield Fix Plus

### Application

The product can be applied by brushing, paint roller or spraying method. For first application two coatings are required.

Interior is supplied ready for use. In case of application via spraying equipment, instructions of the equipment manufacturer must be followed. The product consistency for application on very rough surfaces or by use of spraying equipment can be regulated by adding little water. During application, it is important to maintain the air and object temperature +5°C. This applies equally to the drying period. Sufficient daylight promotes the drying of the UV-cross-linked binding agent. Stir with a stirring gear before application or after long interruptions of work.

Allow a drying period of 6 hours between two individual coats.

### Consumption

The spreading capacity of Interior is approximately 330 ml/m<sup>2</sup>, calculated for two layers, on smooth surfaces of low porosity. The spreading capacity will vary according to the structure and porosity of the surface. If in doubt, a small test area should be applied first.

### Cleaning of tools

Rolls, brushes and spray equipment are to be washed out with water thoroughly immediately after usage.

### Colour

Interior can be tinted with the color systems NCS, RAL and ThermoShield Edition 1.

**Please check color shade before application.**

### Storage and Transport

Interior should be stored and transported cool, but frost-protected. Once opened, close containers firmly and apply as soon as possible. Storable from date of manufacture: 12 months.

### Volume of Supply

2,8 liters; 5 liters; 10 liters; 12,5 liters Differing pack sizes available on request.

### Disposal

Do not empty into canalization, watercourses or the ground. Only completely emptied containers should be disposed for recycling. Please turn part-used products to the collection point in charge.

Non-hazardous waste code according to EU-list of wastes: 080120

### Safety Note

The content of the technical bulletin manifests no contractual legal relation. In any case, the applicant /customer must consider the material's utilizable under practical conditions before application. Do not allow to enter canalization, watercourses or the ground. Keep away from food, drinks and feeding stuff. Keep out of the reach of children. Protect surfaces not to be treated by taking appropriate measures. Avoid contact with skin and eyes. Where applying with spraying method, avoid the inhalation of emerging dust. Before-mentioned information becomes invalid at release of a new technical bulletin due to product improvement. Before- mentioned information was identified by SICC Coatings GmbH in laboratory and practice as guideline values. The product information is given to the best of our knowledge and according to the current state of technology. Environmental influences, materials, application equipment and applications methods are beyond our control and therefore out of our responsibility. SICC©2018

